



TYPICAL SLAB DEPRESSION (U.O.N IN SECTIONS/DETAILS)



NOTES:

- CONTRACTION JOINTS SHALL BE INSTALLED IN SLABS ON GROUND AT A MAXIMUM SPACING IN FEET OF 3 TIMES THE SLAB THICKNESS IN INCHES IN EACH DIRECTION (15'-0" MAXIMUM) BY EITHER OF THE METHODS SHOWN. MAXIMUM LENGTH OF ANY SLAB ON GROUND POUR TO BE 50'-0" BETWEEN CONSTRUCTION JOINTS. THIS SPACING OF JOINTS SHALL APPLY UNLESS SPECIFICALLY SHOWN OTHERWISE ON DRAWINGS.
- REINFORCING TO BE DISCONTINUOUS THROUGH CONSTRUCTION JOINTS.


SLAB ON GROUND JOINTS




NOTES:

- SLAB TO BE 5" MINIMUM (INCLUDING FORM) REINFORCED WITH #4@8" O.C. BOTTOM AND #4@12" O.C. TEMPERATURE. FORM TO BE CORRUGATED GALVANIZED STEEL FORM DECK (GAUGE AS REQUIRED TO SUPPORT WET WEIGHT OF CONCRETE PLUS CONSTRUCTION LOADS. MAXIMUM DEFLECTION OF DECK TO BE 1/240 OF THE SPAN).
- SEE ARCHITECTURAL DRAWINGS FOR DIMENSIONS, SLOPE AND DEPRESSION OF SLAB.

FROST FREE SLAB DETAIL




INFLUENCE ZONE




NOTE: PROVIDE CONCRETE PROTECTION AROUND UTILITY LINE WHEN LINE IS WITHIN FOOTING INFLUENCE ZONE. SEE DETAIL ABOVE FOR INFLUENCE ZONE DEFINITION

FOOTING/GRADE BEAM DETAIL WITH UTILITY LINES BELOW




NOTE: PLACE 2" THICK COMPRESSIBLE FILLER UNIFORMLY AROUND PIPE FULL WIDTH OF GRADE BEAM.

CONDITION 1



NOTE: PLACE 2" THICK COMPRESSIBLE FILLER UNIFORMLY AROUND PIPE FULL WIDTH OF GRADE BEAM.

CONDITION 2




NOTE: IN LIEU OF SLEEVE, WHEN DIRECT PIPE PENETRATION IS REQUIRED, PROVIDE 2" COMPRESSIBLE FILLER UNIFORMLY PLACED AROUND PIPE.

CONDITION 3


NOTE:

- IF LINE IS COMPLETELY BELOW GRADE BEAM, PROVIDE A MINIMUM OF 2" COMPRESSIBLE FILLER ALL AROUND LINE IN THE AREA WHERE THE LINE CROSSES THE GRADE BEAM.
- CONDITIONS 1 AND 2 SHOULD BE AVOIDED AS MUCH AS POSSIBLE. WHERE POSSIBLE, RAISE PIPE TO MEET CONDITION 3 OR LOWER PIPE TO COMPLETELY AVOID PENETRATING GRADE BEAM.

GRADE BEAM REINFORCING DETAIL FOR PENETRATIONS




AT DISCONTINUOUS JOINTS




S.O.G. AT INSIDE CORNERS

SLAB REINFORCING DETAILS (RE-ENTRANT CORNERS)



SLAB ON GROUND - ISOLATION JOINTS WITH PEMB STEEL COLUMNS

NOTE: SEE TYPICAL SLAB ON GROUND JOINT DETAILS, SLAB REINFORCING DETAILS, AND SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS



SLAB ON GROUND DETAIL

BARBER & HOFFMAN, INC.
Consulting Engineers

Cleveland, OH
Columbus, OH
Cranberry Twp., PA

8720 Orion Place, Suite 120
Columbus, OH 43240
614-825-9580/ (F) 614-825-9581
barberhoffman.com

BRAUN & STEIDL architects
Columbus
Akron
234 N. Fifth Street - Columbus, OH 43215 - 614-224-9555 fax 614-224-1506

MULTI-PURPOSE PAVILION
OHIO UNIVERSITY
50 SOUTH GREEN DRIVE - ATHENS, OH 45701-2979
PROJ. NO. OHU-131005

07/01/13

Sheet Issue Date:

Designed: ASK

Drafted: BSA

Checked: NSD

Revisions:

No.	Date	Description

© Copyright 2013
Braun & Steidl Architects

TYPICAL DETAILS

S002

13501